

CAMLOCK ID CHART



TYPE A

MALE CAMLOCK X
FEMALE BSP



TYPE B

FEMALE CAMLOCK X
MALE BSP



TYPE C

FEMALE CAMLOCK X
MALE HOSEBARB



TYPE D

FEMALE CAMLOCK X
FEMALE BSP



TYPE E

MALE CAMLOCK X
MALE HOSEBARB



TYPE F

MALE CAMLOCK X
MALE BSP



TYPE DC

DUST CAP



TYPE DP

DUST PLUG

WORKING PRESSURES

SIZE RANGE (mm)	ALUMINIUM, STAINLESS, BRONZE, BRASS	POLY PROPYLENE, NYGLASS
15	1034kPa	862kPa
20-50	1724kPa	862kPa
65	1034kPa	690kPa
75	862kPa	517kPa
100	690kPa	517kPa
125	517kPa	N/A
150	517kPa	N/A

Ask about our extended range of speciality cams at your local branch

AVAILABLE AT:
IRRI GEAR STORES



www.aapindustries.com.au

AAP SYDNEY - info.nsw@aapindustries.com.au
AAP BRISBANE - info.sqld@aapindustries.com.au
AAP MELBOURNE - info.vic@aapindustries.com.au
AAP ADELAIDE - info.sa@aapindustries.com.au
AAP PERTH - info.wa@aapindustries.com.au
AAP TOWNSVILLE - info.nqld@aapindustries.com.au

MATERIAL	TYPICAL APPLICATION
ALUMINIUM DIECAST (Conforming to ASTM B 26B 26M)	GENERAL USE / AG / INDUSTRIAL
POLY PROPYLENE (BLACK) PP (30% glass filled)	AG SPRAYING EQUIPMENT / CHEMICAL INDUSTRY
NY-GLASS (YELLOW) (30% glass filled)	AG SPRAYING EQUIPMENT / CHEMICAL INDUSTRY
STAINLESS STEEL 316	FOOD INDUSTRY / OFFSHORE / CHEMICAL INDUSTRY