

I.D. INCH	PART No.	WALL THICKNESS MM	TENSILE STRENGTH KG	BURST PRESSURE MPa	WEIGHT KG/MTR	COIL LENGTH MTR
2"	TIH50	2.8	4,700KG	6.5	0.50	200
2 ½"	TIH65	2.9	6,700KG	5.5	0.70	200
3"	TIH76	3.1	8,100KG	5.0	0.95	200
3 ½"	TIH90	3.2	9,100KG	4.0	1.12	200
4"	TIH102	3.2	10,200KG	4.0	1.32	200
4 ½"	TIH114	3.2	11,200KG	3.5	1.43	200
5"	TIH127	3.3	12,200KG	3.0	1.68	200
6"	TIH150	3.4	15,800KG	3.0	1.90	200

Temperature range: -30°C to +75°C



Travelflex

- Highly abrasive resistant for tough Australian conditions
- Process of manufacture ensures an excellent adhesion between rubber and textile
- The nitrile rubber compound is highly resistant to oil and other chemicals
- Resilient and flexible rubber to resist kinking with excellent UV resistance
- Lightweight yet strong
- Pliable for flat storage
- Lower friction - high performance

TEN YEAR WARRANTY



NS-ISO 9001 SERTIFISERT BEDRIFT



POWAFLEX

POLYURETHANE IRRIGATION HOSE

Powaflex P.U. long-life travelling irrigation hose is manufactured from black thermoplastic polyurethane, extruded through a polyester weave. The weave is designed to meet the requirements for high tensile strength and to keep the bending radius to a minimum.

> Temperature range: -50°C to + 75°C. > Standard lengths available up to 300 metres.



I.D. INCH	PART No.	WALL THICKNESS MM	TENSILE STRENGTH KG	BURST PRESSURE MPa	WEIGHT KG/MTR	COIL LENGTH MTR
2"	PPUB50	2.6	5,400	7.0	0.52	200, 300
2½"	PPUB65	2.6	6,500	5.8	0.64	200, 300
3"	PPUB76	2.8	7,900	4.8	0.78	200, 300
3½"	PPUB90	2.9	9,100	4.0	0.95	200, 300
4"	PPUB102	3.0	10,100	3.6	1.16	200, 300
4½"	PPUB114	3.0	10,800	3.4	1.30	200, 300
5"	PPUB127	3.0	12,000	3.2	1.48	200, 300
6"	PPUB152	3.0	14,900	3.2	1.72	200, 300



STRONG DEPENDABLE PERFORMANCE



NS-ISO 9001 SERTIFISERT BEDRIFT