

Customer Value through Innovation



Pipe Fittings

Rural Telescopic Repair Fittings



Rural Telescopic Fittings

The Rural Telescopic Compression Fittings range is Norma Group manufactured with a high level of quality for product peace of mind. These fittings are UV stabilised to ensure they will continue to perform, even in harsh sunlight conditions, and are the ideal connection for repairing and tapping into rural PE pipe. It is easily identified as a rural compression fitting by having green ends. These ends are also interchangeable with the Norma metric fittings.

The telescopic fittings will speed up the process of repairing a broken pipe, while reducing the physical labour involved and the amount of products used. It is no longer necessary to create enough distance between two joiners to flex new pipe in. Simply remove the broken section and use a telescopic fitting by connecting one end and extending the other.



UV Stabilised

- 50 year design life.

Fast Repair

- No need to dig as far to perform a repair job.

Innovative Design

- Dual o-rings are used to reduce chances of leaks.

Green Interchangeable Ends

- Fast identification to ensure you have the correct fitting.

Broad Range

- There is a fitting to adapt to most installations.

Safe and Durable

- Confidence that the fitting will perform.

Parts & Materials

Parts & Materials			
1. Nut	Polypropylene Copolymer	5. Outer Body	Polypropylene Copolymer
2. Clinching Ring	Acetyl	6. Telescopic Nut	Polypropylene Copolymer
3. Barb	Polypropylene Copolymer	7. Insert O-Ring	Nitrile Butadiene Rubber (NBR)
4. Rural O-Ring	Nitrile Butadiene Rubber (NBR)	8. Inner Body	Polypropylene Copolymer



Specifications

- Pressure rating: 850kPa.


Applications

- Repair and maintenance.

Patented Design

- Australian and New Zealand Patented Design No. 2006303813, 567538.

Installation



CUT THE PIPE AS PER THE CUT TEMPLATE

PUSH THE BODY OVER THE INSERT AND TIGHTEN THE NUT

SLIDE THE OUTER BODY OF THE FITTING UNTIL IT GOES OVER THE INSERT AND TIGHTEN THE NUT

SLIP THE NUTS AND CLINCHING RINGS OVER THE PIPES AND TAP THE INSERTS IN

TIGHTEN THE BLACK NUT IN THE MIDDLE OF THE FITTING

PIPE	1"	1 ¼"	1 ½"	2"
MIN CUT AREA	265	310	345	375
MAX CUT AREA	355	410	465	510

Range



Rural Telescopic Joiner - PE x PE

PART NO.	ITEM NO.	SIZE
NXTR133	08370305133	1" X 1"
NXTR144	08370305144	1 1/4" X 1 1/4"
NXTR155	08370305155	1 1/2" X 1 1/2"
NXTR166	08370305166	2" X 2"



Rural Telescopic Tee - PE x PE x PE

PART NO.	ITEM NO.	SIZE
NXTR333	08370305333	1" X 1" X 1"
NXTR344	08370305344	1 1/4" X 1 1/4" X 1 1/4"
NXTR355	08370305355	1 1/2" X 1 1/2" X 1 1/2"
NXTR366	08370305366	2" X 2" X 2"



Rural Telescopic Male End Connector - PE x MI

PART NO.	ITEM NO.	SIZE
NXTR233	08370305233	1" X 1"
NXTR244	08370305244	1 1/4" X 1 1/4"
NXTR255	08370305255	1 1/2" X 1 1/2"
NXTR266	08370305266	2" X 2"



Rural Telescopic Male Tee - PE x MI x PE

PART NO.	ITEM NO.	SIZE
NXTR933	08370305933	1" X 1" X 1"
NXTR944	08370305944	1 1/4" X 1 1/4" X 1 1/4"
NXTR955	08370305955	1 1/2" X 1 1/2" X 1 1/2"
NXTR966	08370305966	2" X 2" X 2"

Related Products



Norma Rural Slipfit Fittings



Guyco Rural Tapping Saddles



Norma Rural Compression Fittings



Guyco Ball Valves



Anka Foot & Check Valves



Guyco Tank Fittings

Customer Value through Innovation



NORMA Pacific Australia

74 Bazalgette Crescent
Dandenong South VIC 3175

Tel: 1300 252 677
Fax: 03 9761 4030

www.normagroup.com.au
sales.au@normagroup.com.au