

# LD PLUS®

Low Density Polyethylene Pipe



Agricultural Applications

Micro Irrigation

Dripper Applications

Hydraulic Automation Applications

Professional Landscaping

## Product Range

Vinidex LD PLUS® provides the best quality Low Density Poly Pipe in the market. LD PLUS® is suitable for use at pressures up to 300kPa at 20°C. LD PLUS® offers the largest range available of LD PE pipes in diameters from 13mm (½”) to 32mm (1¼”) and coil sizes from 25m-200m.

Manufactured to our own high standard, Vinidex LD PLUS® will not split at the fittings. Vinidex LD PLUS® pipe is pressure rated at 300kPa.

Easy to uncoil and lay, Vinidex LD PLUS® pipe is efficient, practical and durable. Suitable for water reticulation, Vinidex LD PLUS® pipe is available from 13mm – 32mm.



Vinidex Code	Nom Size ID	Length	Product Description	Coil Size			Mean coil weight	Pallet QTY
				Inside Diameter	Outside Diameter	Width		
	mm (in)	m		mm	mm		kg	
24105	13 (½)	25	13 LD PLUS PE Irrig Pipe 25m	250	410	85	1.3	120
24115	13 (½)	50	13 LD PLUS PE Irrig Pipe 50m	250	450	110	2.6	50
24120	13 (½)	100	13 LD PLUS PE Irrig Pipe 100m	250	540	135	5.2	40
24130	13 (½)	300	13 LD PLUS PE Irrig Pipe 300m	250	740	190	15.6	12
24170	19 (¾)	25	19 LD PLUS PE Irrig Pipe 25m	430	580	105	2.1	40
24177	19 (¾)	50	19 LD PLUS PE Irrig Pipe 50m	430	650	125	4.1	40
24180	19 (¾)	100	19 LD PLUS PE Irrig Pipe 100m	520	820	180	8.2	12
24190	19 (¾)	200	19 LD PLUS PE Irrig Pipe 200m	520	880	250	16.4	8
24195	25 (1)	50	25 LD PLUS PE Irrig Pipe 50m	820	1080	120	6.3	10
24205	25 (1)	100	25 LD PLUS PE Irrig Pipe 100m	820	1170	160	12.5	7
24200	25 (1)	200	25 LD PLUS PE Irrig Pipe 200m	820	1220	250	25.0	5
24231	32 (1¼)	200	32 LD PLUS PE Irrig Pipe 200m	900	1420	270	41.9	-

## Pressure Rating Data

Vinidex LD PLUS® is capable of withstanding a working pressure of 300kPa (3 Bar) where temperatures of the pipe and water are not more than 35°C.

If operating temperatures are more than 35°C, the pressure rating of the pipe reduces as indicated in this table.

40°C – 280kPa


45°C – 220kPa

50°C – 170kPa

55°C – 130kPa

60°C – 100kPa

## Micro-Irrigation Pipe Friction Loss



This chart was developed using the Colebrook-White Formula with a roughness coefficient of  $k = 0.015$  as quoted in AS 2200-2006 "Design Charts for Water Supply and Sewerage".





Vinidex Pty Limited  
ABN 42 000 664 942

## CUSTOMER SERVICE

Phone: 13 11 69

Fax: 13 24 43

Email: [sales@vinidex.com.au](mailto:sales@vinidex.com.au)

Web: [www.vinidex.com.au](http://www.vinidex.com.au)



## AUSTRALIAN OPERATIONS

### Sydney

254 Woodpark Rd  
Smithfield NSW 2164

### Adelaide

9–11 Kaurna Ave  
Edinburgh SA 5111

### Townsville

49 Enterprise St  
Bohle QLD 4818

### Darwin

3846 Marjorie St  
Pinelands NT 0829

### Wagga Wagga

280 Byrnes Rd  
Wagga Wagga  
NSW 2650

### Launceston

15 Thistle St  
Sth Launceston TAS 7249

### Toowoomba

Lot 2 Witmack Rd  
Wellcamp QLD 4350

### Perth

Sainsbury Rd  
O'Connor WA 6163

### Melbourne

Unit 1, 10 Duerdin St  
Notting Hill VIC 3168

### Brisbane

224 Musgrave Rd  
Coopers Plains QLD 4108

### Rodney Industries

19 Valente Close  
Chermside QLD 4032

231-245 St Albans Rd  
Sunshine VIC 3020

#### Limitation of Liability

This product catalogue has been compiled by Vinidex Pty Limited ("the Company") to promote better understanding of the technical aspects of the Company's products to assist users in obtaining from them the best possible performance. The product catalogue is supplied subject to acknowledgement of the following conditions:

1 The product catalogue is protected by copyright and may not be copied or reproduced in any form or by any means in whole or in part without prior consent in writing by the Company.  
2 Product specifications, usage data and advisory information may change from time to time with advances in research and field experience. The Company reserves the right to make such changes at any time without further notice. All care has been taken to develop this chart and to check its accuracy. However, Vinidex can not be held responsible for any design failures resulting from the use of the chart as design involves many inputs and decisions which are outside our control. Water Authorities, Departments of Primary Industries or Agriculture and Private Consultants provide excellent design services. The reader is encouraged to make use of their services. 3 Correct usage of the Company's products involves engineering judgements, which can not be properly made without full knowledge of all the conditions pertaining to each specific installation. The Company expressly disclaims all and any liability to any person whether supplied with this publication or not in respect of anything and all of the consequences of anything done or omitted to be done by any such person in reliance whether whole or part of the contents of this publication. 4 No offer to trade, nor any conditions of trading, are expressed or implied by the issue of content of this product catalogue. Nothing herein shall override the Company's Condition of Sale, which may be obtained from the Registered Office or any Sales Office of the Company. 5 This product catalogue is and shall remain the property of the Company, and shall be surrendered on demand to the Company. 6 Information supplied in this product catalogue does not override a job specification, where such conflict arises; consult the authority supervising the job. © Copyright Vinidex Pty Limited.